

## 1.2L/4.8 Dz

### Video Cable 75 Ω



### Application

Video cables are primarily used in closed circuit TV systems and in studio applications.

### Standards

For analogue and digital video signals (Composite, Component, SDI, SDV, SDTI, HDTV)

### Flame resistance

Not for fixed installation for construction works

### Construction

Inner conductor	stranded copper wire, diameter 1.2 mm
Insulation	Foam-PE, diameter 4.8 mm
Outer conductor	2xCu-braid, tinned
Sheath	DMC FLEX PUR, PUR, diameter 7.2 mm green, RAL 6018
Printing	<b>DRAKA</b> COMTEQ - 1.2L/4.8Dz - 75 Ω ± 1% - HDTV

### Electrical properties

at 20°C

DC resistance	Inner conductor	21 Ω/km
	Outer conductor	5 Ω/km
Mutual capacitance		56 pF/m
Characteristic impedance		75 Ω ± 0.75 Ω
Velocity ratio		67 %
Screening factor		> 90 dB

# 1.2L/4.8 Dz

## Electrical data

at 20°C

Attenuation (dB/100m)		Return loss (dB)	
Frequency (MHz)		Frequency (MHz)	
1	0.5	50 – 300	> 26
10	1.9	300 – 3000	> 22
100	8.0	3000 – 3500	> 18
200	10.1	3500 – 500	> 15
300	14.0		
500	17.3		
800	22		
1000	25.8		
1500	32		
2250	41.6		
3000	49		
3500	54.4		
4000	57.1		
4500	62.2		
5000	67.1		

## Technical data

Product code	Type	Weight kg/km	Standard delivery length m	Drum size *PWD	Copper content	Tensile force N	Bending radius mm	Storage
1002456 CT2878800	1.2L/4.8Dz Flex PUR gn	80	1000	600/200/3 10	80	115	45	inside

\*PWD (plywood drum)

## Product Code Table

Product Description	Product Code	PG Reference Code	PG Part Number
DR 1.2L/4.8DZ DMC FLEX PUR HDTV		60016740	<b>60016740</b>
DR 1.2L/4.8DZ DMC FLEX PUR HDTV 1000DW	1002456-01000DW	60016740	<b>60016741</b>

© PRYSMIAN GROUP 2006, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.